Default public web root

If you installed Mixpost using the Standalone method you may instruct your web server(Nginx/Apache/Anything else) the default public web root.

You should set the default public web root to the "/public" folder of the Mixpost Standalone project.

Nginx

In Ubuntu/Debian, you can find the:

- The main configuration file in "**/etc/nginx/nginx.conf**"
- Default server block: "**/etc/nginx/sites-available/default**"
- Other server blocks (virtual hosts): Additional files in "**/etc/nginx/sites-available/**" and they are symlinked to "**/etc/nginx/sites-enabled/**" when activated.

```
server {
    listen 80;
    root /var/www/your-mixpost-project/public;
    index index.php index.html;


    // your nginx configs
}
```

Remember, after making changes to any Nginx configuration file, you should restart the Nginx service to apply the changes.

```
sudo systemctl restart nginx
```

Apache

In Ubuntu, you can find the default virtual host: "**/etc/apache2/sites-available/000-default.conf**".

```
<VirtualHost *:80>
    ServerAdmin webmaster@yourdomain.com
```

```
    DocumentRoot "/var/www/your-mixpost-project/public"
    ServerName yourdomain.com
    ServerAlias www.yourdomain.com


    <Directory "/var/www/your-mixpost-project/public">
        Options Indexes FollowSymLinks
        AllowOverride All
        Require all granted
    </Directory>


    // your apache configs
</VirtualHost>
```

Remember, after making changes to any Apache configuration file, you should restart (or reload) the Apache service to apply the changes.

```
sudo systemctl restart apache2
sudo systemctl reload apache2
```

Plesk

Open your Plesk panel, then go to "**Hosting settings**". Change the "**Document root**" value to match the "public" folder.

Revision #3
Created 16 June 2023 12:50:19 by Dima Botezatu
Updated 25 October 2023 14:33:35 by Dima Botezatu